

TSX Series High-Performance Blood Bank Refrigerators



Our high-performance blood bank refrigerators are designed to meet strict requirements established by the AABB for the storage of whole blood and blood components.

- Factory pre-set to 4°C to meet blood storage guidelines
- Triple pane glass door helps maintain optimal internal condition
- Forced-air circulation for temperature uniformity and fast temperature recovery
- Heat-free defrost for maximum temperature uniformity
- Convenient, stainless steel, fully extendable and adjustable drawers
- Standard, built-in chart recorder
- Quiet operation at just 52 dBA
- Four 2" casters for easy mobility; the front two are lockable
- Bright, LED interior lighting
- Keyed on/off switch with easy to use, setpoint security
- Self-closing door with 90° stop to assist with inventory loads
- Built-in remote alarm contacts
- See pages 13–15 for options and accessories



TSX Series high-performance blood bank refrigerators

Model no.	Temp. range (setpoint)	Capacity cu. ft./liters (blood bags*)	Electrical (plug)	Doors	Drawers	Defrost	Certification	Interior dimensions D x W x H in. (cm)	Exterior dimensions D x W x H in. (cm)	Shipping weight lbs. (kg)
TSX2304BA			115V, 60Hz (NEMA 5-15)				UL, cUL			575 (261)
TSX2304BD	2–8°C (4°C)	23/650 (385)	208-230V, 60Hz (NEMA 6-15)	1 glass	7	auto	UL, cUL	28.5 x 24 x 58 (72.3 x 61 x 147.3)	37 x 28 x 78.6 (94 x 71.1 x 199.6)	554 (251)
TSX2304BV			230V, 50Hz (European)				UL, cUL, CE			554 (251)

*450 mL whole blood bags