# versatile and reliable

Thermo Scientific TSC Series chest freezers contain all the sample protection features of our TSE and TSD upright series. Choose a -86°C or -40°C cabinet in four convenient sizes as well as a full range of racking solutions.

#### Rugged construction for everyday use

- Heavy gauge, cold-rolled steel cabinets with a powder coat paint finish for a uniform exterior that resists chipping and rust.
- 5" (127mm) foamed-in-place, polyurethane insulation reduces power consumption, maintains temperature setpoint and combined with sub lids and door gasket, provides longer holding time in the event of a power failure.
- State-of-the-art, refrigeration system improves temperature control and increases reserve capacity, resulting in a more stable temperature sample.
- Stainless steel interior.
- 1" (2.5cm) access ports allow for the use of independent probes or instrumentation.




### **Optional CO2 or** LN2 back-up

Optional choice of CO2 or LN2 safety back-up systems for additional sample protectioin in the event of a power or mechanical failure.



#### Microprocessor control

Centralized information center. including microprocessor control and monitoring system ensures that all controls and displays are easy to reach and read. Knee level on the 3 cu. ft. (85L) models.




### **Polystyrene** interiorsub-lids

Reduce cold air loss and improve temperature recovery after door openings.



#### Single-hand operation

Easy-to-use, ergonomic, lockable door handle.



#### Simplified installation

With our new easy-roll 2" (5cm) locking casters.

### RS-485 and 4-20 milliamp analog outputs

For independent monitoring devices and recorders.



#### Easy-to-remove, washable filter

Provides protection from dust on condenser, reducing the risk of refrigeration malfunction or risk to samples

## Thermo Scientific TSC Series -86°C Chest Freezers

Model No.	Capacity cu. ft. (liters)	2 in. Box Qty.	Electrical	Amps / Breaker (Plug)	Interior Dimensions H x W x D in. (cm)	Exterior Dimensions H x W x D in. (cm)	Shipping Weight lbs. (kg)
TSC390A TSC390V	3.0 (85)	63	115V / 60Hz 230V / 50Hz	10.5/20 (NEMA 5-20) 5.4/15 (European)	16.5 x 18.5 x 18.5 (41.69 x 47.0 x 47.0)	43.8 x 28.5 x 29.9 (113.3 x 72.4 x 75.9)	432 (196)
TSC1390A TSC1390D TSC1390V	12.7 (360)	252	115V / 60Hz 208-230V / 60Hz 230V / 50Hz	16/20 (NEMA 5-20) 12/15 (NEMA 6-15) 12/15 (European)	28.0 x 42.5 x 18.5 (71.1 x 108.0 x 47.0)	40.5 x 72.0 x 33.4 (102.9 x 182.9 x 84.8)	716 (325)
TSC1790A TSC1790D TSC1790V	17.0 (481)	348	115V / 60Hz 208-230V / 60Hz 230V / 50Hz	16/20 (NEMA 5-20) 12/15 (NEMA 6-15) 12/15 (European)	28.0 x 58.8 x 18.5 (71.1 x 149.4 x 47.0)	40.5 x 87.6 x 33.8 (102.9 x 222.5 x 85.9)	821 (372)
TSC2090A TSC2090D TSC2090V	20.0 (566)	396	115V / 60Hz 208-230V / 60Hz 230V / 50Hz	16/20 (NEMA 5-20) 12/15 (NEMA 6-15) 12/15 (European)	28.0 x 66.5 x 18.5 (71.1 x 168.9 x 47.0)	40.5 x 96.0 x 33.4 (102.9 x 243.8 x 84.8)	833 (378)

# Thermo Scientific TSC Series -40°C Chest Freezers (-10°C to -40°C)

Model No.	Capacity cu. ft. (liters)	2 in. Box Qty.	Electrical	Amps / Breaker (Plug)	Interior Dimensions H x W x D in. (cm)	Exterior Dimensions H x W x D in. (cm)	Shipping Weight lbs. (kg)
TSC350A TSC350V	3.0 (85)	63	115V / 60Hz 230V / 50Hz	5/15 (NEMA 5-20) 3/15 (European)	16.5 x 18.5 x 18.5 (41.69 x 47.0 x 47.0)	43.8 x 28.5 x 29.9 (113.3 x 72.4 x 75.9)	395 (179)
TSC1350A TSC1350D TSC1350V	12.7 (360)	252	115V / 60Hz 208-230V / 60Hz 230V / 50H	6.5/15 (NEMA 5-20) 6.5/15 (NEMA 6-15) 6.5/15 (European	28.0 x 42.5 x 18.5 (71.1 x 108.0 x 47.0)	40.5 x 72.0 x 33.4 (102.9 x 182.9 x 84.8)	659 (299
TSC1750A TSC1750D TSC1750V	17.0 (481)	348	115V / 60Hz 208-230V / 60Hz 230V / 50Hz	6.5/15 (NEMA 5-20) 6.5/15 (NEMA 6-15) 6.5/15 (European	28.0 x 58.8 x 18.5 (71.1 x 149.4 x 47.0)	40.5 x 87.6 x 33.8 (102.9 x 222.5 x 85.9)	764 (34
TSC2050A TSC2050D TSC2050V	20.0 (566)	396	115V / 60Hz 208-230V / 60Hz 230V / 50H	6.5/15 (NEMA 5-20) 6.5/15 (NEMA 6-15) 6.5/15 (European)	28.0 x 66.5 x 18.5 (71.1 x 168.9 x 47.0)	40.5 x 96.0 x 33.4 (102.9 x 243.8 x 84.8)	776 (352)

# **Monitoring and Remote Options**

Model No.	Electrical	Description
5612-1A 5612-3V	120V / 60Hz 230V / 50Hz	Remote Alarm with Audible Signal Extend the freezer's on-board alarm systems to remote locations in the facility
400047 400182	120V / 60Hz 220V / 50Hz	<b>Sensaphone Telephone Dialing System</b> Monitors up to four channels and dials up to four telephone numbers. A dedicated telephone line is required. Not approved for sales requiring CE.
400134 400183	120V / 60Hz 220V / 50Hz	<b>Sensaphone Telephone Dialing System</b> Monitors up to eight channels and dials up to eight telephone numbers. A dedicated telephone line is required. Not approved for sales requiring CE.
400048 400049	120V / 60Hz 220V / 50Hz	<b>Temperature / Power Monitor</b> External digital and audible/visual alarm monitors temperature and power supply of the freezer. Includes temperature probes.

# **Options**

Model No.	Installation	Description			
1950447	Factory	LN2 Back-Up System Maintains temperature down to -80°C with liquid nitrogen			
1950448	Field	LNZ Back-op System Maintains temperature down to -80 C with highlight			
1950445	Factory	<b>CO2 Back-Up System</b> Maintains temperature down to -70°C with CO2			
1950446	Field	OOZ Back-Op System Maintains temperature down to -70 0 Mun 002			
201241	Factory	Chart Recorder			
201240	Field	6" (150mm), seven day recorder to -150°C. Includes box of chart paper (quantity: 50)			
398213	RS-232 (0-1)				
398214	RS-485 (0-1V)	Data Outputs (Factory-Installed Only)			
398215	RS-485 (0-5V)				
195967	Factory	Water-Cooled Condenser Option for -86°C Chest Freezers See page 24 for details.			

# Accessories

Model No.	Description
195947	Replacement Air Filter for 3 cu. ft. (84.9L) Chest Freezers (quantity: 5)
195948	Replacement Air Filter for Other Chest Freezers (quantity: 5)
17020	Ink Chart Paper (quantity: 50)
400159	Replacement Back-Up Battery
245231	Red Felt Tip Pen
245232	Blue Felt Tip Pen
4425	Cryo Gloves (medium)
4426	Cryo Gloves (large)
4000401	LN2 Transfer Hose – flexible 6' metal hose: 0.5" diameter, 45° flare with swivel end
950316	Wall Clamp - CO2 cylinder holder for securing tank to the wall for OSHA guidelines
991505	<b>High-Pressure Liquid C02 Hose</b> – 6' long, kink-resistant, stainless steel lined, double-braided sheath. 316 stainless steel NPT F fitting. Maximum working pressure 2,500 psig.

### **Chest Freezer Racks**

Model No. (Description)	Dimensions W x D x H in. (cm)	Freezer Vol. cu. ft. (liters)	Boxes/ Rack (Plates)	Racks/ Freezer (Plates)	Boxes/ Freezer (Plates)
398184 (2" Box Rack with locking rod)	5.5 x 5.5 x 15.2 (14 x 14 x 38.6)	3.0 (85)	7	9	63
398186 (2" Box Rack with locking rod)	5.5 x 5.6 x 26.5 (14 x 14.2 x 67.3)	12.7 (360) 17.0 (481) 20.0 (566)	12 12 12	21 29 33	252 348 396
398185 (3" Box Rack)	5.5 x 5.5 x 16 (14 x 14 x 40.6)	3.0 (85)	5	9	45
398187 (3" Box Rack)	9.4 x 5.5 x 26.5 (14 x 14 x 67.3)	12.7 (360) 17.0 (481) 20.0 (566)	8 8 8	21 29 33	168 232 264
398188 (27 Position Microplate Rack)	5.3 x 3.5 x 25.8 (13.5 x 8.9 x 65.5)	12.7 (360) 17.0 (481) 20.0 (566)	(27) (27) (27)	(33) (48) (51)	(891) (1,296) (1,377)
114048 (Wire Basket with Rollers)*	11.8 x 16.5 x 12.3 (29.9 x 41.9 x 31.2)	12.7 (360) 20.0 (566)	N/A	5 9	N/A
189001 189000 (Basket Rail Set)	11.8 x 16.5 x 12.3 (29.9 x 41.9 x 31.2)	12.7 (360) 20.0 (566)	N/A	N/A	N/A


**See Page 19 for Boxes and Dividers** 



2" Box Rack Model No. 398184



3" Box Rack Model No. 398185




2" Box Rack Model No. 398186



Wire Basket Model No. 114048



3" Box Rack Model No. 398187



Microplate Rack Model No. 398188