

Designed to achieve your next breakthrough

The **Thermo Scientific™ Heracell™ VIOS series** represents a new era in advanced incubator design for sensitive cultures like stem and primary cells in leading research, pharmaceutical and clinical laboratory applications.

Through a holistic approach to culturing, our newest incubator series provides everything necessary for your most demanding and highly critical applications. By combining our latest technology advancements in contamination control and uniform growth conditions with existing proven and reliable features, you are now able to achieve your goals faster, more reliably, and with less effort.

Better solutions for optimal cell growth

Revolutionary THRIVE™ active airflow technology delivers homogeneous growth conditions fast, avoiding unwanted sample variation.

Complete contamination control

Proven protection from every direction including ISO class 5 HEPA filtered air, on-demand high-temperature sterilization, and easy to maintain copper.

Enhanced simplicity

Designed to focus on convenience, allowing you to spend more time on your research and less time managing your incubator.

The Heracell VIOS CO₂ incubator delivers the performance reliability, ease of operation, and value required to support a range of culturing needs from basic research to demanding, leading-edge applications, so you're ready for whatever comes next!



A direct heat CO₂ incubator that better supports you and your science.




- 165L (5.8 cu ft) in a compact foot print, readily stackable
- Choice of electropolished stainless steel or 100% pure copper
- Adjustable, perforated shelving
- Easy-to-clean, coved corners with convenient access port
- Reversible exterior door for added flexibility
- 2 year parts and labor warranty

Better solutions for optimal cell growth

The Heracell VIOS incubator incorporates THRIVE active airflow technology, providing faster recovery and uniformity for consistent results. Your cells experience total recovery of all critical growth parameters in **less than 10 minutes following a door opening.***

Innovative THRIVE active airflow technology

In-chamber fan gently and evenly distributes clean, humidified air throughout the chamber ensuring all cells experience the same conditions without the threat of desiccation.



Incoming air first travels over a direct heated water reservoir resulting in 50% faster humidity recovery than with a standard water pan design.**

The in-line HEPA filter cleans the airstream of microbes and particles protecting cultures from contamination.

The precise, variable speed fan with an auto-stop function disables fan operation during door openings to minimize air exchange. Once the door is closed, the fan temporarily accelerates for quick recovery.

* Based on internal testing standards for a 30 second door opening, recovery time calculated to 98% of starting value for temperature and CO₂ and 95% of starting value for humidity

**Comparison of internal testing data to published specifications



| optimal cell growth



Advanced *in situ* sensor technology

Probes and gas sensors are positioned in the chamber to respond quickly to any deviations in desired conditions

- Robust design allows maintenance-free, *in situ* location, eliminating the need for removal during sterilization and separate cleaning and handling activities
- **New!** Dual temperature probes with PID controller provide over temperature protection by preventing overshoot during recovery; temperatures recover under 5 minutes*
- Oxygen controlled models are equipped with advanced zirconium oxide sensors, enabling a choice of control ranges 1-21% (hypoxic) and 5-90% (hyperoxic)
- On-demand auto-start facilitates easy start-up and calibration

Save valuable incubator space with
Thermo Scientific Nunc EasyFill
Cell Factory systems.

www.thermoscientific.com/easyfill


* Temperature recovery time calculated to 98% of starting value, based on internal testing standards of a 30 second door opening

Choice of accurate and reliable CO₂ sensor technology

Temperature resistant, bulb-free IR CO₂ sensor with MEMS emitter technology

New temperature resistant IR180Si infrared CO₂ sensor replaces the traditional incandescent IR light source with silicon MEMS emitter technology that improves stability and reliable service life. This sensor is ideal for labs looking for the best of both technologies for advanced, high volume, or value culturing.

- Internal auto-calibration eliminates drift due to changes in ambient conditions that can affect traditional IR sensors
- IR180Si CO₂ measurement not affected by changes in temperature, humidity, oxygen, or barometric pressure**
- Highly responsive with recovery under 5 minutes from door openings




A traditional IR sensor contains an incandescent bulb that puts out less light as it ages, resulting in sensor drift. The IR180Si eliminates this problem. Our silicon MEMS emitter is designed to retain intensity over time, lasting up to 50% longer than ordinary IR sensors.

Innovative TC sensor solution

The NEW TC180 offers the performance advantages of traditional IR technologies without the limiting lifespan of a standard incandescent bulb. This sensor is ideal for everyday cell culture applications.

- Improved stability with internal humidity compensation minimizing drift between calibrations
- CO₂ values unaffected by changes in humidity, enabling fast recovery from a routine door opening
- Economical, long service life



*CO₂ recovery time calculated to 98% of starting value, based on internal testing standards of a 30 second door opening


**Information cited based on sensor manufacturer's data

TC180 – CO₂ recovery under 6 minutes from a door opening of 30 seconds.

Added culturing flexibility with variable oxygen control

Many cell types thrive best in CO₂ incubators with reduced oxygen. Culturing cells at lower oxygen concentration will better simulate physiological conditions, resulting in cell behaviors that are more predictive of the *in vivo* environment.

Our variable oxygen control (or “tri-gas”) incubators will generate conditions to help your cells grow faster and healthier. With the Heracell VIOS incubator, you can select the incubator for your O₂ range: simulate hypoxic (1-21%) environments for primary cell, stem cell and embryo research applications, or hyperoxic (5-90%) conditions for research in lung, retina and other sensitive tissues.



Primary Cell Growth in Atmospheric and Physiological Oxygen

Cells cultured in low oxygen (hypoxia) will generally grow faster, live longer, and show lower stress.


Adapted from Parrinello et al. Nature Cell Biology 2003.

With segmented inner doors, accessing separate sections of the incubator is convenient, minimizing recovery time and contamination risk.

"Our lab mandates this [5% oxygen in the tri-gas incubator] in order to mimic conditions in the body, so that cells are as close to those conditions as possible and nothing is different. All of the signals for proper epigenetics are there."

Stem cell researcher at biomedical research institute





Recessed covered humidity pan

Exclusive condensation free humidification system

Our unique integral covered humidity reservoir maximizes relative humidity without condensation ensuring a dry inner chamber, preventing a breeding ground for contaminants.

- Providing stable, high relative humidity levels, the integrated 3 liter reservoir allows more space for samples than standard pan designs
- The reservoir cover eliminates standing water in the culture area while limiting particles and spilled media from settling into the reservoir
- Water level is continuously monitored and displayed on the Thermo Scientific iCAN™ touchscreen with advanced notice of refill needed
- Humidity reservoir may be filled without removing shelves or cultures and is easily drained through built-in copper drain
- CO₂ and optional N₂/O₂ gases are pre-humidified before entering the chamber, providing a more constant, uniform environment


Evaporation is 4X faster at 80% than at > 93% humidity*. Maximum humidity with rapid recovery is critical to limit water evaporation from media that results in toxic concentrations.

*Esser, P and Weitzmann, L. Evaporation From Cell Culture Plates. Thermo Scientific 2011, TILSPNUNCBU02 0111

Directly heated reservoir boosts 5X faster recovery than removable pan designs.

Relative humidity recovery is less than 10 minutes with 30 second door opening.**

**Humidity recovery time calculated to 95% of starting value, based on internal testing standards of a 30 second door opening.



Complete **contamination control**

Protect your cultures with proven technologies

Our advanced contamination control technologies are designed to protect your valuable cultures, eliminate the loss of time and resources while providing convenient added security for your research work.

Heracell VIOS incubators deliver the latest innovations in contamination control technologies that protect the incubator air, surfaces and humidification water. Cultures are continuously protected 24/7, and convenient on-demand high temperature sterilization offers simplified cleaning protocols.

**“Normal” indoor air contains
30-700 microorganisms/m³.***
**Normal flora on our skin equals
10,000 microorganism/cm².****
**These can enter your incubator
during routine door openings.**

* Stryjowska-Sekulska et al. 2007.

** Grice et al. 2008

Expand the growth of even your most finicky cells with specialty coated Thermo Scientific™ EasYFlasks™, featuring a unique angled neck for full access to the growth surface when pipetting.


www.thermoscientific.com/easyflasks



High-temperature sterilization with push button simplicity

Our exclusive Thermo Scientific Steri-Run™ high temperature sterilization cycle reaches 180°C on all chamber surfaces and is independently proven to achieve total sterilization and a 12 log Sterility Assurance Level (SAL). With the push of a button, the simple overnight routine provides fast, easy elimination of microbial contaminants and eliminates the need for separate autoclaving of parts.

- Fully automatic 180°C cycle assures total, uniform sterilization of all chamber surfaces (12 log SAL)
- Independent third party tests prove elimination of biological contaminants including fungal mold, vegetative and spore forms of bacteria, including mycoplasma
- Avoids the physical constraints and variation associated with UV germicidal lamps and the ongoing costs, handling and storage of potentially toxic germicides



The U.S. and E.U. Pharmacopeias no longer recommend a given temperature and time for sterilization. Instead, they require proof of performance. To meet requirements of a 12 log SAL, a 6 log reduction of biological indicator endospores must be demonstrated in half the time.

Validation that all surfaces reach 180°C with 47 point test on all chamber areas including the glass door and shelves.

Microorganisms Eliminated During the Steri-Run cycle*

Microorganism	ATCC #	Average Positive Control*	Number Recovered*	Log Reduction*
<i>Aspergillus brasiliensis</i>	16404	2.98x10 ⁴	NG**	-4.5
<i>Escherichia coli</i>	25922	2.22x10 ⁴	NG	-4.3
<i>Mycoplasma pneumoniae</i>	15531	1.25x10 ⁶	NG	-6.1
<i>Bacillus atrophaeus</i> spores	51189	2.16x10 ⁷	NG	-7.3
<i>Geobacillus stearothermophilus</i> spores	12980	4.81x10 ⁶	NG	-6.7

*Average based on 3 independent tests performed on different days.

** NG = No Growth


Independent third party testing proved the Steri-Run cycle, when heated to 180C for 45 minutes, eliminated all microorganisms validating that the full 90-minute cycle meets requirements for a >12 log sterility assurance level (SAL).

HEPA Air Filtration for Air Purity

Airborne particulates are a primary source of contamination in most lab settings. Our advanced HEPA filter technology protects your cultures, providing Class ISO-5 clean room-like air quality conditions within only five minutes after a 30-second door opening.

- Chamber air is processed every 60 seconds to ensure air quality
- Featuring a space saving configuration, the HEPA filter is readily replaceable with minimal cost

HEPA filters are rated for their efficiency of capturing 0.3 μm sized particles, since this is the most penetrating size. In fact, larger and smaller particles are caught even more efficiently, over 99.998%



Security for your cells. The HEPA filter provides a 4 log reduction of particles in 5 minutes. ISO 5 clean room air quality achieved in 5 minutes from a door opening.

easy to maintain

Easy to maintain 100% solid copper

More cell culture professionals are choosing Thermo Scientific incubators with 100% pure copper interiors.

- Easy-to-clean, no special handling required
- Corrosion resistant copper surfaces provide long service life and are safe for cultured cells
- Durability, reliability, and recyclability makes copper a smart, sustainable choice

"Everything we do is cell based. The main thing I've noticed is my ability to maintain my cells. There is just no comparison since we got the copper. I've had stainless steel incubators before but the comfort level you can have with the copper is simply amazing."

Laboratory Manager with 14 years experience working with all types of mammalian cell lines, including adherent, suspension, hybridomas and transformed stem cells

Enhanced Simplicity

The Heracell VIOS series was designed to simplify your interaction with the incubator. Spend more time pursuing your science and less time managing your equipment.

Main screen with a bright LED display provides at-a-glance monitoring even from a distance.


iCAN™ Touchscreen Interface

Total control at your fingertips

The intelligent iCAN interface provides complete data visibility to monitor all incubator interaction, featuring door-mounted position for easy access, on-screen menu prompts, error and usage logs, data logging, performance trend graphing and multiple language selection.

New rH monitoring assures the proper humidity level with blue, full line icon. Low water alarm indicates critical low humidity levels requiring water addition.

ISO 5 icon indicates the chamber has reached clean room air quality, protecting your cultures.



The on-demand data and error logs screen of the Heracell VIOS 160i incubator displays the following information:

Loop	Date	Time	Error	801/802
RH	25.02.14	09:28:08	No water	
RH	24.02.14	16:07:55	No water	
SYS	24.02.14	15:38:18	Error fan	
SYS	24.02.14	15:33:48	Error fan	
RH	24.02.14	15:32:49	No water	
SYS	24.02.14	14:41:33	Error fan	
SYS	18.02.14	08:28:54	Error fan	
SYS	17.02.14	14:42:48	Error fan	
SYS	17.02.14	14:08:24	Error fan	
SYS	17.02.14	12:53:27	Error fan	
SYS	10.02.14	16:48:48	Error auto-start	

Buttons: End, Continue

▲ **On-demand data and error logs** provide a downloadable history of activity and conditions including parameter changes and alarms.



Optimized chamber design for easy maintenance and monitoring

- Conveniently manage reminders for HEPA filter, Steri-Run sterilization cycle and Autostart automatic calibration functions
- Programmable access code ensures additional security of your settings and information
- Selectable languages simplify operation: English, Spanish, German, French, Italian, Japanese and Mandarin
- For easier water handling, humidity reservoir may be filled or drained without the removal of shelves or cultures
- Easy-to-clean, coved corners with convenient access port
- No special tools required for assembly and disassembly of interior components




Data collection

Retire your laboratory notebook, data collection is easy with a Heracell VIOS incubator. A data collection software disc is supplied with each unit, to facilitate data capture from the unit's convenient rear mounted USB output port.

Optional 4-20 mA signal output is available for interfacing with external data collection systems, such as Thermo Scientific™ Smart Vue™ remote monitoring system which is ideal for GMP environments with external sensors and CFR-21 compliant software packages.

construction	Chamber volume	165L (5.8 cu.ft.)
	Interior chamber	electropolished stainless steel or 100% solid copper
	Exterior chamber	18 gauge (1 mm), cold-rolled steel, powder coated
	Access port	42 mm diameter
	Data outputs	remote alarm contacts, USB, and optional 4-20 mA
dimensions	Internal dimensions (w x h x d)	470 x 607 x 576 mm
		18.5 x 23.9 x 22.7 inches
	External dimensions (w x h x d)	637 x 900 x 880 mm
		25.1 x 35.4 x 34.6 inches
	Shipping dimensions (w x h x d)	755 x 1010 x 1205 mm
	Operating weight	83 kg (without accessories), (183 lbs)
shelves	Shipping weight	98 kg, (216 lbs)
	Dimensions (w x d)	423 x 465 mm (16.7 x 18.3 in)
	Number standard/maximum	3/10
	Max. load per shelf/total load	10/30 kg (22/66 lbs)
electrical	Construction	perforated, adjustable
	Rated voltage	1/N/PE AC ($\pm 10\%$), 230, 220V, 120V, 100V
	Nominal kW consumption (Steri-Run)	0.56 (1.06) – 230V, 0.51 (0.97) – 220V
		0.55 (1.01) - 120V, 0.39 (0.72) – 100V
	Rated frequency	50/60 Hz
temperature	Heat emission to environment at 37°C	0.06 kWh/h
	During Steri-Run:	0.26 kWh/h (average), 0.78 kWh/h (heating time), 0.59 kWh/h (hold time)
sterilization cycle	Control	$\pm 0.1^{\circ}\text{C}$
	Range	Range 3°C above ambient to 55°C
	Uniformity	$< \pm 0.3^{\circ}\text{C}$
	Ambient range	$18\ldots 34^{\circ}\text{C}$
	Tracking alarm	$\pm 1^{\circ}\text{C}$
humidity	Cycle temperature	180°C on all internal surfaces
	Cycle duration	Under 12 hours
CO ₂	RH	$>93\%$ @ 37°C
	Humidity reservoir	max. 3L / min 0.5L
O ₂	Control	$\pm 0.1\%$
	Range	1-20%
	Tracking alarm	$\pm 1\%$
	Inlet pressure	12-15 PSI (0.8-1.0 bar)
	Gas purity	min. 99.5 or medical quality
	CO ₂ inlet	1/8" hose (barbed)
O ₂	Control	$\pm 0.1\%$
	Range	1-21% or 5-90%
	Tracking alarm	$\pm 1\%$
	Inlet pressure	12-15 PSI (0.8-1.0 bar)
	Gas purity	min. 99.5 or med. quality
	O ₂ inlet	1/8" hose (barbed)

Select the Heracell VIOS incubator that best meets your culturing needs



Units are easily stackable. Required stacking adapter provides efficient heat dissipation to operate Steri-Run in one unit while culturing in the other without process disruption.



Heracell VIOS 160i CO₂ Incubator

Stainless Steel

100% Copper

TC Sensor

Single Chamber with TC CO₂ Sensor, 100V 50/60Hz *

51030299

51030298

Single chamber with TC CO₂ sensor, 120V 50/60Hz

51030285

51030284

Single chamber with TC CO₂ sensor, 230V 50/60Hz

51030287

51030286

Dual chamber with TC CO₂ sensor, stacking adapter, and roller dolly 120V 50/60Hz

50144906

50144908

Dual chamber with TC CO₂ sensor, stacking adapter, and roller dolly 230V 50/60Hz

50145502

50145503

IR Sensor

Single chamber with IR CO₂ Sensor, 100V 50/60Hz *

51030634

51030633

Single chamber with IR CO₂ sensor, 120V 50/60Hz

51030475

51030472

Single chamber with IR CO₂ sensor, 230V 50/60Hz

51030478

51030476

Dual chamber with IR CO₂ sensor, stacking adapter, and roller dolly 120V 50/60Hz

50145504

50145516

Dual chamber with IR CO₂ sensor, stacking adapter, and roller dolly 230V 50/60Hz

50145515

50145517

* For 100V units, the left hinged door orientation is standard

Options and accessories to customize your Heracell VIOS CO₂ incubatorsHeracell VIOS 160i CO₂ Incubatorfactory
installed

Country Versions

Electrical configuration for Switzerland	51900300
Electrical configuration for Great Britain	51900303
Electrical configuration for Italy	51900306
Electrical configuration for Australia	51900449
Electrical configuration for Denmark	51900481
Electrical configuration for China	51900900

Chamber Configuration

Internal 4-20 mA analog data output	51901143
Left hinge door configuration	51900293
Internal gas guard for CO ₂	51900735
Internal gas guard for N ₂ /O ₂	51900736
Stainless steel external outer casing	51901126
3 door inner gas tight screen (replaces single inner door configuration)	51901144

O₂ Control

1-21% O ₂ control	51901137
5-90% O ₂ control	51901138
1-21% O ₂ control with 3 door inner gas tight screen door	51901145
5-90% O ₂ control with 3 door inner gas tight screen door	51901146

customer
installed

Support Frames, Stacking Adapters and Shelving

Support frame for double chamber, 172 mm high (with castors)	50145394
Support frame for double chamber, 200 mm high (without castors)	50145435
Support frame for single chamber, 780 mm high (without castors)	50145436
Adaptor required for stacking 160i models	50144550
Stacking adaptor configured to stack a Heracell VIOS on top of Heracell 150i	50145437
Support frame with drawers for single chamber, 780 mm high with 3 drawers complete with 4 swivel locking castors	50056459
Additional stainless steel shelf, full-width, 2 support rails	50051909
Additional shelf, solid copper, full-width, with 2 support rails	50051910
Set of 3 HERAtrays, 1/3 width, in stainless steel (autoclaveable)	50051913
Set of 3 HERAtrays, 1/3 width, in solid copper	50051914
Set of 2 HERAtrays, 1/2 width, in stainless steel (autoclaveable)	50058672
Set of 2 HERAtrays, 1/2 width, in copper	50061050

CO₂/O₂ Accessories and Monitoring

Replacement in chamber HEPA filter	50141920
Door lock retrofit kit, key entry, to prevent unauthorized access (requires service installation in field)	50145438
CO ₂ gas regulator, 2-stage, for gas tank	3429937
N ₂ gas regulator, 2-stage for gas tank	3429942
O ₂ gas regulator, 2-stage for gas tank	3429943
External gas guard automatic change-over to reserve tank, 120 V, 50/60 Hz	50059043
External gas guard automatic change-over to reserve tank, 230 V, 50/60 Hz	50046033
IR gas tester with travel case (for advanced calibration and testing purposes)	50121515
IR gas tester interface kit	50122015
5 inlet port filters for IR testers	50060287

