

Thermo Scientific Thermolyne Premium Large Muffle Furnaces

Robust design and choice of four temperature controllers, ideal for industrial applications including ashing organic and inorganic samples and conducting gravimetric analysis



Includes: Models F6010 and F6018 include a cord and plug set
Required Accessories: All models except F6010 and F6018 require hardwiring
Warranty*: 1 year (parts and labor)
Certifications: All units CSA approved, -33 units also CE marked

- Spacious 14L (0.5 cu. ft.) capacity and reaches a maximum of 1200°C
- Four heating elements are located on the chamber top, bottom and sides for enhanced temperature uniformity
- Built-in vent port removes undesirable contaminants and moisture to extend the life of the element and unit
- Rear of the chamber incorporates a 0.312 in. diameter port for monitoring chamber temperatures with independent measuring devices
- Optional stainless-steel shelf doubles load capacity (maximum temperature of 900°C)
- Door safety switch stops power to heating elements when door opens
- Thermocouple break protection cuts power to the heating elements, preventing a thermocouple failure runaway condition
- Furnaces with B1, C1, and D1 control also use a mechanical over-temperature protection relay

Choice of Temperature Controllers

- **A1:** Digital single setpoint control; single display shows actual temperature or setpoint
- **B1:** Digital single setpoint control with single ramp to setpoint and a dwell; single display shows actual temperature or setpoint
- **C1:** Digital programmable control with one stored program of eight segments
- **D1:** Digital programmable control with four stored programs, 16 segments per program and Controller includes RS-232 communications

Cat. No.	Capacity	Temp. Range	Temp. Stability/ Uniformity at 1000°C	Interior D x W x H	Exterior L x W x H	Control	Electrical	Shipping Weight
F6018	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±0.3°C ±2.2°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	A1	208V 50/60Hz 11.2A 2325w	60.8kg (134 lb.)
F6010*	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±0.3°C ±2.2°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	A1	240V 50/60Hz 12.9A 3095w	60.8kg (134 lb.)
F6028C	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±1.5°C ±4.5°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	B1	208V 50/60Hz 19.2A 4000w	60.8kg (134 lb.)
F6020C	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±1.5°C ±4.5°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	B1	240V 50/60Hz 18.3A 4400w	60.8kg (134 lb.)
F6020C-33	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±1.5°C ±4.5°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	B1	240V 50/60Hz 18.3A 4400w	60.8kg (134 lb.)
F6028C-80	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±1.5°C ±4.5°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	C1	208V 50/60Hz 19.2A 4000w	60.8kg (134 lb.)
F6020C-80	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±1.5°C ±4.5°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	C1	240V 50/60Hz 18.3A 4400w	60.8kg (134 lb.)
F6020C-33-80	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±1.5°C ±4.5°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	C1	240V 50/60Hz 18.3A 4400w	60.8kg (134 lb.)
F6038CM	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±1.5°C ±4.5°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	D1	208V 50/60Hz 19.3A 4000w	60.8kg (134 lb.)
F6030CM	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±1.5°C ±4.5°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	D1	240V 50/60Hz 18.3A 4400w	60.8kg (134 lb.)
F6030CM-33	14L (0.5 cu.ft.)	100° to 1200°C (212° to 2192°F)	±1.5°C ±4.5°C	25 x 33 x 18cm (10 x 12.8 x 6.8in.)	51 x 48.5 x 53.3cm (20.1 x 19.1 x 21in.)	D1	240V 50/60Hz 18.3A 4400w	60.8kg (134 lb.)

* Available with plug and cord for China: order F6010CN

Accessories

Cat. No.	Description
JSX16	Shelf Pegs (4 required)
PH177X1	Hearth Tray, 22.9 x 27.3 x 1.9cm (one per chamber floor)
PHX1	Hearth Tray, 8.2 x 10.1 x 1.27cm (up to 9 per chamber floor in 3x3 pattern)
SH408X1	Stainless-steel Shelf (requires 4 shelf pegs)