

# Designed for your everyday laboratory needs

The Thermo Scientific™ TSG Series general purpose laboratory refrigerators and chromatography refrigerators are designed with your needs in mind. The TSG series is ideal for the demanding requirements of daily use in research, clinical, and industrial laboratories storing reagents, media, proteins, and samples used daily in the lab.

The TSG Series general purpose refrigerators and chromatography refrigerators are built with the performance, security, and quality features you have come to expect from Thermo Scientific:

- EPA ENERGY STAR® certified
- Whisper-quiet refrigeration systems
- Safety sensor protected interior outlet on chromatography models
- Temperature, power failure, and door ajar alarms
- Green, natural refrigerants
- 2 year parts and labor, plus 3 year compressor warranty



# Built with the performance, security, and quality you've come to expect



## Performance

- New 2° to 10° C cabinet temperature range (5°C factory setpoint)
- 51 dBA whisper-quiet operation
- Low heat output
- Adaptive defrost
- Digital controller
- ENERGY STAR certified
- Green refrigerants

## Security

- High and Low temperature alarms (audible and visual)
- Door ajar alarm (except 45 cu. ft. sliding glass door models)
- Power failure alarm with battery back-up
- Remote alarm contacts
- Keyed door locks
- Hydrocarbon safety sensor protected interior duplex outlet (chromatography models only)

## Quality

- 2 years parts and labor, plus 3 year compressor warranty
- cULus certified
- Painted steel exterior in white or gray
- Stainless steel interior available on some models
- Reduced compressor cycle time improves reliability
- Made in the USA in a zero-waste-to-landfill facility



# TSG Series Refrigerators



TSG Series general purpose refrigerators are designed with your laboratory in mind, combining the performance, security, and quality required for everyday laboratory applications.

- Featuring a wide range of cabinet sizes from 12 cu. ft. to 72 cu. ft.
- Whisper-quiet operation at 51 dBA
- ENERGY STAR certified
- Adaptive defrost
- Glass (double pane) or solid door configurations
- Choice of white painted interior and exterior, or stainless steel interior and gray exterior
- LED interior lighting
- Temperature, door ajar, and power failure (with battery back-up) alarms
- Digital controller
- Low heat output
- Rear access port
- Keyed door lock(s)
- Remote alarm contacts

**TSG Series General Purpose Refrigerators**

| Model no. | Temp. range (setpoint) | Capacity cu. ft. (liters) | Electrical (plug)      | Doors         | Exterior/ Interior Color | Shelves                            | Defrost  | Certification      | Exterior dimensions D x W x H in. (mm) | Interior dimensions D x W x H in. (mm) | Shipping weight lbs. (kg)           |                                      |
|-----------|------------------------|---------------------------|------------------------|---------------|--------------------------|------------------------------------|----------|--------------------|----------------------------------------|----------------------------------------|-------------------------------------|--------------------------------------|
| TSG12RPGA | 2-10 °C (5°C)          | 12 (339)                  | 115V, 60Hz (NEMA 5-15) | 1 Glass       | white/white              | 4                                  | Adaptive | cULus, ENERGY STAR | 25 x24.75 x 75.8 (635 x 629 x 1926)    | 20.75 x 21 x 45.75 (527 x 533 x        | 230 (105)                           |                                      |
| TSG25RPGA |                        | 23 (651)                  |                        |               |                          |                                    |          |                    | 32 x 27.75 x 81 (813 x 705 x 2057)     | 28.5 x 24 x 61.75 (724 x 610 x 1569)   | 392 (178)                           |                                      |
| TSG30RPGA |                        | 27 (764)                  |                        | 2 Slide Glass |                          | 8                                  |          |                    | 32 x 30.75 x 81 (813 x 781 x 2057)     | 28.5 x 27 x 61.75 (724 x 686 x 1569)   | 386 (175)                           |                                      |
| TSG45RPLA |                        | 45 (1274)                 |                        |               |                          |                                    |          |                    | 2 Glass                                | 32 x 52.7 x 81 (813 x 1339 x 2057)     | 27 x 49 x 61.75 (686 x 1245 x 1569) | 561 (255)                            |
| TSG49RPGA |                        | 49 (1387)                 |                        |               |                          |                                    |          |                    |                                        | 3 Glass                                | 32 x 75.7 x 81 (813 x 1924 x 2057)  | 28.5 x 72 x 61.75 (724 x 1829 x      |
| TSG72RPGA | 72 (2038)              |                           |                        |               |                          |                                    |          |                    |                                        |                                        |                                     |                                      |
| TSG25RPSA | 2-10 °C (5°C)          | 23 (651)                  | 115V, 60Hz (NEMA 5-15) | 1 solid       | white/white              | 4                                  | Adaptive | cULus, ENERGY STAR | 32 x 27.75 x 81 (813 x 705 x 2057)     | 28.5 x 24 x 61.75 (724 x 610 x 1569)   | 392 (178)                           |                                      |
| TSG30RPSA |                        | 27 (764)                  |                        | 8             |                          | 32 x 30.75 x 81 (813 x 781 x 2057) |          |                    | 28.5 x 27 x 61.75 (724 x 686 x 1569)   | 386 (175)                              |                                     |                                      |
| TSG49RPSA |                        | 49 (1387)                 |                        |               |                          | 2 solid                            |          |                    | 32 x 52.7 x 81 (813 x 1339 x 2057)     | 27 x 49 x 61.75 (686 x 1245 x 1569)    | 597 (271)                           |                                      |
| TSG25RSGA | 2-10 °C (5°C)          | 23 (651)                  | 115V, 60Hz (NEMA 5-15) | 1 Glass       | gray/ stainless steel    | 4                                  | Adaptive | cULus, ENERGY STAR | 32 x 27.75 x 81 (813 x 705 x 2057)     | 28.5 x 24 x 61.75 (724 x 610 x 1569)   | 392 (178)                           |                                      |
| TSG30RSGA |                        | 27 (764)                  |                        |               |                          |                                    |          |                    | 2 Slide Glass                          | 8                                      | 32 x 30.75 x 81 (813 x 781 x 2057)  | 28.5 x 27 x 61.75 (724 x 686 x 1569) |
| TSG45RSLA |                        | 45 (1274)                 |                        | 2 Glass       |                          | 32 x 52.7 x 81 (813 x 1339 x 2057) |          |                    |                                        |                                        | 27 x 49 x 61.75 (686 x 1245 x 1569) | 561 (255)                            |
| TSG49RSGA |                        | 49 (1387)                 |                        |               |                          | 3 Glass                            |          |                    | 12                                     |                                        | 32 x 75.7 x 81 (813 x 1924 x 2057)  | 28.5 x 72 x 61.75 (724 x 1829 x      |
| TSG72RSGA |                        | 72 (2038)                 |                        |               |                          |                                    |          |                    |                                        |                                        |                                     |                                      |
| TSG25RSSA | 2-10 °C (5°C)          | 23 (651)                  | 115V, 60Hz (NEMA 5-15) | 1 solid       | gray/ stainless steel    | 4                                  | Adaptive | cULus, ENERGY STAR | 32 x 27.75 x 81 (813 x 705 x 2057)     | 28.5 x24 x 61.75 (724 x 610 x 1569)    | 392 (178)                           |                                      |
| TSG30RSSA |                        | 27 (764)                  |                        | 8             |                          | 32 x 30.75 x 81 (813 x 781 x 2057) |          |                    | 28.5 x27 x 61.75 (724 x 686 x 1569)    | 386 (175)                              |                                     |                                      |
| TSG49RSSA |                        | 49 (1387)                 |                        |               |                          | 2 solid                            |          |                    | 32 x 52.7 x 81 (813 x 1339 x 2057)     | 28.5 x 49 x61.75 (724 x 1245 x 1569)   | 597 (271)                           |                                      |

## TSG Series Refrigerators Accessories Ordering Guide

| For use with refrigerator size                                  | 12 cu. ft.<br>(339L) | 23 cu. ft.<br>(651 L) | 27 cu. ft.<br>(764 L) | 45 cu. ft.<br>(1447 L) | 49 cu. ft.<br>(1387 L) | 72 cu. ft.<br>(2038 L) |
|-----------------------------------------------------------------|----------------------|-----------------------|-----------------------|------------------------|------------------------|------------------------|
| Customer-Installed Accessories                                  | Model No.            | Model No.             | Model No.             | Model No.              | Model No.              | Model No.              |
| Full Shelf with Clips (1 white wire shelf and 4 mounting clips) | 7510TA               | 7511TA                | AY2100X1              | AY2095X26              |                        | AY2102X2               |
| Full Shelf with Clips (1 gray wire shelf and 4 mounting clips)  |                      | 7512TA                | 7513TA                | AY2098X1               |                        | 7514TA                 |
| Half Shelf with Clips (1 white wire shelf and 4 mounting clips) |                      |                       | AY2020X2              | 7520TA                 |                        | AY2102X1               |
| Half Shelf with Clips (1 gray wire shelf and 4 mounting clips)  |                      |                       | 7518TA                | 7521TA                 |                        | 7522TA                 |
| 6" 7-day inkless chart recorders, -40°C to +25°C                |                      |                       | Model no. (all sizes) |                        |                        |                        |
| Free-standing, customer-installed, 115V, 60Hz models            | 6383-7A              |                       |                       |                        |                        |                        |
| Replacement chart paper, box of 50                              | 6184                 |                       |                       |                        |                        |                        |



Smart Tracker wireless monitoring device



Thermo Scientific™ TSG505 under counter refrigerator



Thermo Scientific Samco Clicktainer Vials and specimen containers

Visit **thermofisher.com** for accessories, wireless monitoring, consumables, media, reagents and more.

Australia: +61 39757 4300  
Austria: +43 1 801 40 0  
Belgium: +32 53 73 42 41  
China: +800 810 5118 or  
+400 650 5118  
France: +33 2 2803 2180  
Germany national toll-free: 0800 1 536 376  
Germany international: +49 6184 90 6000

India toll free: 1800 22 8374  
India: +91 22 6716 2200  
Italy: +39 02 95059 552  
Japan: +81 3 5826 1616  
Netherlands: +31 76 579 55 55  
New Zealand: +64 9 980 6700  
Nordic/Baltic/CIS Countries:  
+358 9 329 10200

Russia: +7 812 703 42 15  
Spain/Portugal: +34 93 223 09 18  
Switzerland: +41 44 454 12 12  
UK/Ireland: +44 870 609 9203  
USA/Canada: +1 866 984 3766  
Other Asian Countries: +852 2885 4613  
Countries not listed: +49 6184 90 6000

**ThermoFisher**  
SCIENTIFIC